

12v 10Ah

CHARGERS

	ITEM	UNIT	SPECIFICATION	REMARK
INPUT				
01	Rating Input Voltage	V ac	100~240Vac 50-60Hz	
02	Input voltage range	V ac	90~264Vac	
03	Rating Input Current	A	1.5Arms	
04	Max.input power	W	150	
OUTPUT				
05	Rating output voltage	V dc	13.8V	
06	Output voltage range	V dc	10VDC~15VDC	
INPUT				
01	Rating Input Voltage	V ac	100~240Vac 50-60Hz	
02	Input voltage range	V ac	90~264Vac	
03	Rating Input Current	A	1.5Arms	
04	Max.input power	W	150	
OUTPUT				
05	Rating output voltage	V dc	13.8V	
06	Output voltage range	V dc	10VDC~15VDC	
07	Suit with Battery type		12V 20AH-100AH VRLA	
08	Charging current(stage1)	A	10.0±1.0@12V	
09	Charging voltage(stage2)	V	14.5V±0.2V	
10	Floating voltage(stage3)	V	13.7V±0.15V	
04	Max.input power	W	150	
OUTPUT				
05	Rating output voltage	V dc	13.8V	
06	Output voltage range	V dc	10VDC~15VDC	
07	Suit with Battery type		12V 20AH-100AH VRLA	
08	Charging current(stage1)	A	10.0±1.0@12V	
09	Charging voltage(stage2)	V	14.5V±0.2V	
10	Floating voltage(stage3)	V	13.7V±0.15V	
11	Cut-off current(stage2→3)	A	<2.0+-0.20A	
12	Typical charging time	hour	8	
13	Max.output power	W	120W	
14	Hold-on time	ms	NC	Input:220Vac Output:Full load
15	Ripple current	mA	200	Input:220Vac Output:Full load
16	LED color		Red:charging Green:finish/Idle	
17	Output protect	-	OCP&OVP&Reverse input protection	
18	Efficiency	%	75%(min)	At max.load
Environment				
19	Operate temperature	℃	0~+40	Full load&natural convection
20	Operate humidity	%RH	20~90	Relative humidity,non-condensing.
21	Storage temperature	℃	-40~+70	
22	Storage humidity	%RH	10~95	Relative humidity,non-condensing.
23	Cooling	-	Natural convection	
24	Temperature factor	%	--	
25	Vibration resistance		5MM/50HZ/600S	Non-operating condition.

12v 10Ah